

























Test level	Use for				For comparison *)				Type of weapon (example)	Bullet	Test ammunition specifications				Extracts from test conditions		
	VPAM PM 2007	VPAM BRV 2009	VPAM BSW 2006	VPAM HVN 2009	DIN EN 1063	DIN EN 1522/23	VPAM BRV 1999	STANAG 4569 AEP55			Calibre	Type	Mass [g]	Manufacturer Type	Firing distance s [m]	Missile speed v [m/s]	Missile energy E [J]
1	PM 1	VR 1	BSW 1	HVN 1	BR 1	FB 1	VR 1				22 LR	L/RN	2,6	Winchester	10 ± 0,5	360 ± 10	168
2	PM 2	VR 2	BSW 2	HVN 2							9mm Luger	FMJ/RN/SC	8,0	DAG DM 41	5 ± 0,5	360 ± 10	518
3	PM 3	VR 3	BSW 3	HVN 3	BR 2	FB 2	VR 2				9mm Luger	FMJ/RN/SC	8,0	DAG DM 41	5 ± 0,5	415 ± 10	689
4	PM 4	VR 4	BSW 4	HVN 4	BR 3	FB 3	VR 3				357 Mag.	FMJ/CB/SC	10,2	Geco	5 ± 0,5	430 ± 10	943
					BR 4	FB 4	VR 4				44 Rem.Mag.	FMJ ³⁾ /FN/SC	15,6	Speer Nr. 4459	5 ± 0,5	440 ± 10	1510
5	PM 5	VR 5	BSW 5	HVN 5							357 Mag.	FMs/CB	7,1	DAG Spezial	5 ± 0,5	580 ± 10	1194
6	PM 6	VR 6	BSW 6	HVN 6							7,62 x 39	FMJ/PB/FeC	8,0	PS	10 ± 0,5	720 ± 10	2074
7	PM 7	VR 7	BSW 7	HVN 7	BR 5	FB 5	VR 5	Level 1 ^{***)}			223 Rem. (5,56x45mm)	FMJ/PB/SCP	4,0	MEN SS 109	10 ± 0,5	950 ± 10	1805
					BR 6	FB 6	VR 6				308 Win. (7,62x51mm)	FMJ/PB/SC	9,55	MEN DM 111	10 ± 0,5	830 ± 10	3289
8	PM 8	VR 8	BSW 8	HVN 8				Level 2			7,62 x 39	FMJ/PB/HCI	7,7	BZ	10 ± 0,5	740 ± 10	2108
9	PM 9	VR 9	BSW 9	HVN 9	BR 7	FB 7	VR 7				308 Win. (7,62x51mm)	FMJ/PB/HC	9,7	FNB P 80	10 ± 0,5	820 ± 10	3261
10	PM 10	VR 10	BSW 10	HVN 10				Level 3			7,62 x 54 R	FMJ/PB/HCI	10,4	B32	10 ± 0,5	860 ± 10	3846

*) The norms DIN EN 1063 (special glazing in construction) and DIN EN 1522/23 (windows and doors) as well as STANAG 4569 AEP 55 and VPAM BRV 1999 are indicated for comparison. Requirements and test conditions deviate in some cases from VPAM.

**) If necessary regarding missile speed, oscillation and impact point, the shooting distance can be adapted for test levels 1-10.

***) Level 1, if shot in addition with 5,56 x 45 mm (Type: M193)

****) FMJ steel full jacket, FMJ*) copper full jacket, CB cone tip head, RN round head, PB pointed head, FN flat head, L full lead, SC lead soft core, FeC iron core, SCP lead soft core with steel penetrator, HC steel hard core, FMs full brass, I Incendiary